

Safety Data Sheet

according to Regulation (EC) No 1907/2006



PU140

Revision date: 11.02.2024

Page 1 of 10

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

PU140

Further trade names

PU 140

UFI: VS00-Q0YK-J00E-SWUQ

1.2. Relevant identified uses of the substance or mixture and uses advised against

Use of the substance/mixture

Paints and varnishes

1.3. Details of the supplier of the safety data sheet

Company name: Hottinger Brüel & Kjaer
Street: Im Tiefen See 45
Place: D-64293 Darmstadt
Telephone: +49 (0)6151 803-0
Internet: www.hbm.com
Responsible Department: +49(0)6131 19240 support@hbm.com

1.4. Emergency telephone number:

+353 1014670

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

Regulation (EC) No 1272/2008

Flam. Liq. 3; H226

Carc. 1B; H350

Full text of hazard statements: see SECTION 16.

2.2. Label elements

Regulation (EC) No 1272/2008

Hazard components for labelling

butanone oxime; ethyl methyl ketoxime; ethyl methyl ketone oxime

Signal word: Danger

Pictograms:



Hazard statements

H226 Flammable liquid and vapour.
H350 May cause cancer.

Precautionary statements

P201 Obtain special instructions before use.
P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
P280 Wear protective gloves/protective clothing/eye protection/face protection/hearing protection.

Special labelling of certain mixtures

Safety Data Sheet

according to Regulation (EC) No 1907/2006



PU140

Revision date: 11.02.2024

Page 2 of 10

EUH208 Contains butanone oxime; ethyl methyl ketoxime; ethyl methyl ketone oxime, Cobaltoctoat.
May produce an allergic reaction.
Restricted to professional users.
Restricted to professional users.

Labelling of packages where the contents do not exceed 125 ml

Signal word: Danger

Pictograms:



Hazard statements

H350

Precautionary statements

P201-P280

2.3. Other hazards

No information available.

SECTION 3: Composition/information on ingredients

3.2. Mixtures

Hazardous components

CAS No	Chemical name	Quantity		
	EC No	Index No	REACH No	
	GHS Classification			
90622-57-4	Isoparaffinische Kohlenwasserstoff (Alkane, C9-12-iso-)		25 - 50 %	
	292-459-0			
96-29-7	butanone oxime; ethyl methyl ketoxime; ethyl methyl ketone oxime		< 1 %	
	202-496-6	616-014-00-0		
	Carc. 1B, Acute Tox. 3, Acute Tox. 4, Skin Irrit. 2, Eye Dam. 1, Skin Sens. 1, STOT SE 1, STOT SE 3, STOT RE 2; H350 H301 H312 H315 H318 H317 H370 H336 H373			
136-52-7	Cobaltoctoat		< 0,25 %	
	205-250-6			
	Eye Irrit. 2, Skin Sens. 1, Aquatic Acute 1, Aquatic Chronic 3; H319 H317 H400 H412			

Full text of H and EUH statements: see section 16.

Specific Conc. Limits, M-factors and ATE

CAS No	EC No	Chemical name	Quantity	
	Specific Conc. Limits, M-factors and ATE			
90622-57-4	292-459-0	Isoparaffinische Kohlenwasserstoff (Alkane, C9-12-iso-)	25 - 50 %	
	oral: LD50 = >10000 mg/kg			
96-29-7	202-496-6	butanone oxime; ethyl methyl ketoxime; ethyl methyl ketone oxime	< 1 %	
	dermal: ATE 1100 mg/kg; oral: ATE 100 mg/kg			

SECTION 4: First aid measures

4.1. Description of first aid measures

General information

Remove affected person from the danger area and lay down. If unconscious but breathing normally, place in recovery position and seek medical advice. First aider: Pay attention to self-protection!

Safety Data Sheet

according to Regulation (EC) No 1907/2006



PU140

Revision date: 11.02.2024

Page 3 of 10

After inhalation

Provide fresh air. In case of respiratory tract irritation, consult a physician.

After contact with skin

After contact with skin, wash immediately with plenty of water and soap. Remove contaminated, saturated clothing immediately. In case of skin irritation, consult a physician.

After contact with eyes

In case of contact with eyes flush immediately with plenty of flowing water for 10 to 15 minutes holding eyelids apart and consult an ophthalmologist.

After ingestion

If swallowed, rinse mouth with water (only if the person is conscious). If swallowed, do not induce vomiting: seek medical advice immediately and show this container or label.

4.2. Most important symptoms and effects, both acute and delayed

No information available.

4.3. Indication of any immediate medical attention and special treatment needed

No information available.

SECTION 5: Firefighting measures

5.1. Extinguishing media

Suitable extinguishing media

Water spray jet, Dry extinguishing powder, Foam

Unsuitable extinguishing media

Full water jet

5.2. Special hazards arising from the substance or mixture

Collect contaminated fire extinguishing water separately. Do not allow entering drains or surface water.

5.3. Advice for firefighters

Wear a self-contained breathing apparatus and chemical protective clothing.

Co-ordinate fire-fighting measures to the fire surroundings.

Additional information

Use water spray jet to protect personnel and to cool endangered containers. Suppress gases/vapours/mists with water spray jet. Collect contaminated fire extinguishing water separately. Do not allow entering drains or surface water.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

General advice

Do not breathe gas/vapour/aerosol.

Provide adequate ventilation as well as local exhaust at critical locations.

If technical exhaust or ventilation measures are not possible or insufficient, respiratory protection must be worn.

Use personal protection equipment.

Personal protection equipment: see section 8

For non-emergency personnel

Remove persons to safety.

For emergency responders

First aider: Pay attention to self-protection!

6.2. Environmental precautions

Do not allow to enter into surface water or drains.

Do not allow uncontrolled discharge of product into the environment.

6.3. Methods and material for containment and cleaning up

Safety Data Sheet

according to Regulation (EC) No 1907/2006



PU140

Revision date: 11.02.2024

Page 4 of 10

For cleaning up

Absorb with liquid-binding material (sand, diatomaceous earth, acid- or universal binding agents).
Take up mechanically, placing in appropriate containers for disposal.

6.4. Reference to other sections

Safe handling: see section 7
Wear personal protection equipment (refer to section 8).
Disposal: see section 13

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Advice on safe handling

If local exhaust ventilation is not possible or not sufficient, the entire working area should be ventilated by technical means.

Advice on protection against fire and explosion

No special technical protective measures are necessary.

Further information on handling

Wear personal protection equipment (refer to section 8). Do not empty into drains. When using do not eat, drink, smoke, sniff.

7.2. Conditions for safe storage, including any incompatibilities

Requirements for storage rooms and vessels

Keep container tightly closed in a cool, well-ventilated place.

Further information on storage conditions

No information available.

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

Occupational exposure limits

CAS No	Substance	ppm	mg/m ³	fib/cm ³	Category	Origin
96-29-7	Methyl ethyl ketoxime	3	10		TWA (8 h)	
		10	33		STEL (15 min)	

8.2. Exposure controls



Appropriate engineering controls

If handled uncovered, arrangements with local exhaust ventilation should be used if possible.
If local exhaust ventilation is not possible or not sufficient, the entire working area should be ventilated by technical means.

Protective and hygiene measures

When using do not eat or drink. Do not breathe gas/fumes/vapour/spray.
After contact with skin, take off immediately all contaminated clothing, and wash immediately with plenty of water and soap. Wear suitable protective clothing, gloves and eye/face protection.
Draw up and observe skin protection programme.

Eye/face protection

Wear eye/face protection.

Safety Data Sheet

according to Regulation (EC) No 1907/2006



PU140

Revision date: 11.02.2024

Page 5 of 10

Hand protection

When handling with chemical substances, protective gloves must be worn with the CE-label including the four control digits. EN ISO 374

The quality of the protective gloves resistant to chemicals must be chosen as a function of the specific working place concentration and quantity of hazardous substances.

Thickness of the glove material: $\geq 0,7$ mm

Suitable gloves type NBR (Nitrile rubber)

Breakthrough time: >480 min

For special purposes, it is recommended to check the resistance to chemicals of the protective gloves mentioned above together with the supplier of these gloves.

Skin protection

Used working clothes should not be worn outside the work area. Separate storage of work clothes.

Respiratory protection

If technical exhaust or ventilation measures are not possible or insufficient, respiratory protection must be worn. Filtering device (full mask or mouthpiece) with filter: a

Environmental exposure controls

Do not allow to enter into surface water or drains.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Physical state:	Liquid
Colour:	transparent
Odour:	Solvents
pH-Value:	not determined

Changes in the physical state

Melting point/freezing point:	not determined
Boiling point or initial boiling point and boiling range:	150 °C
Sublimation point:	not determined
Softening point:	not determined
Pour point:	not determined
not determined:	

Flash point:	46 °C
Sustaining combustion:	No data available

Flammability

Solid/liquid:	not determined
---------------	----------------

Explosive properties

not determined

Lower explosion limits:	0,6 vol. %
Upper explosion limits:	7 vol. %
Auto-ignition temperature:	230 °C

Self-ignition temperature

Solid:	not determined
Gas:	not determined
Decomposition temperature:	not determined

Oxidizing properties

not determined

Safety Data Sheet

according to Regulation (EC) No 1907/2006



PU140

Revision date: 11.02.2024

Page 6 of 10

Vapour pressure: (at 20 °C)	< 1 hPa
Vapour pressure:	not determined
Density:	not determined
Bulk density:	not determined
Water solubility:	not determined
Solubility in other solvents	
not determined	
Partition coefficient n-octanol/water:	not determined
Viscosity / dynamic:	not determined
Viscosity / kinematic:	not determined
Flow time:	not determined
Relative vapour density:	not determined
Evaporation rate:	not determined
Solvent separation test:	not determined
Solvent content:	51 %

9.2. Other information

Solid content:	0,25 %
No information available.	

SECTION 10: Stability and reactivity

10.1. Reactivity

No information available.

10.2. Chemical stability

The substance is chemically stable under recommended conditions of storage, use and temperature.

10.3. Possibility of hazardous reactions

No hazardous reaction when handled and stored according to provisions.

10.4. Conditions to avoid

No information available.

10.5. Incompatible materials

No information available.

10.6. Hazardous decomposition products

No information available.

SECTION 11: Toxicological information

11.1. Information on hazard classes as defined in Regulation (EC) No 1272/2008

Acute toxicity

Based on available data, the classification criteria are not met.

ATEmix calculated

ATE (oral) 11111 mg/kg; ATE (dermal) > 2000 mg/kg; ATE (inhalation vapour) > 20 mg/l; ATE (inhalation dust/mist) > 5 mg/l

Safety Data Sheet

according to Regulation (EC) No 1907/2006



PU140

Revision date: 11.02.2024

Page 7 of 10

CAS No	Chemical name				
	Exposure route	Dose	Species	Source	Method
90622-57-4	Isoparaffinische Kohlenwasserstoff (Alkane, C9-12-iso-)				
	oral	LD50 >10000 mg/kg	Ratte	JAT	
96-29-7	butanone oxime; ethyl methyl ketoxime; ethyl methyl ketone oxime				
	oral	ATE 100 mg/kg			
	dermal	ATE 1100 mg/kg			

Irritation and corrosivity

Based on available data, the classification criteria are not met.

Sensitising effects

Based on available data, the classification criteria are not met.

Contains butanone oxime; ethyl methyl ketoxime; ethyl methyl ketone oxime, Cobaltoctoat. May produce an allergic reaction.

Carcinogenic/mutagenic/toxic effects for reproduction

May cause cancer. (butanone oxime; ethyl methyl ketoxime; ethyl methyl ketone oxime)

Germ cell mutagenicity: Based on available data, the classification criteria are not met.

Reproductive toxicity: Based on available data, the classification criteria are not met.

STOT-single exposure

Based on available data, the classification criteria are not met.

STOT-repeated exposure

Based on available data, the classification criteria are not met.

Aspiration hazard

Based on available data, the classification criteria are not met.

11.2. Information on other hazards

Endocrine disrupting properties

This product does not contain a substance that has endocrine disrupting properties with respect to non-target organisms as no components meets the criteria.

SECTION 12: Ecological information

12.2. Persistence and degradability

No information available.

12.3. Bioaccumulative potential

No information available.

12.4. Mobility in soil

No information available.

12.5. Results of PBT and vPvB assessment

The substances in the mixture do not meet the PBT/vPvB criteria according to REACH, annex XIII.

12.6. Endocrine disrupting properties

This product does not contain a substance that has endocrine disrupting properties with respect to non-target organisms as no components meets the criteria.

12.7. Other adverse effects

No information available.

Further information

No information available.

SECTION 13: Disposal considerations

Safety Data Sheet

according to Regulation (EC) No 1907/2006



PU140

Revision date: 11.02.2024

Page 8 of 10

13.1. Waste treatment methods


Disposal recommendations

Dispose of waste according to applicable legislation.

SECTION 14: Transport information

Land transport (ADR/RID)


14.1. UN number: UN 1263
14.2. UN proper shipping name: PAINT
14.3. Transport hazard class(es): 3
14.4. Packing group: I
Hazard label: 3



Classification code: F1
Special Provisions: 163 367 650
Limited quantity: 500 mL
Excepted quantity: E3
Transport category: 1
Hazard No: 33
Tunnel restriction code: D/E

Inland waterways transport (ADN)


14.1. UN number: UN 1263
14.2. UN proper shipping name: Paint
14.3. Transport hazard class(es): 3
14.4. Packing group: I
Hazard label: 3



Classification code: F1
Special Provisions: 163 367 650
Limited quantity: 500 mL
Excepted quantity: E3

Marine transport (IMDG)

14.1. UN number: UN 1263
14.2. UN proper shipping name: PAINT
14.3. Transport hazard class(es): 3
14.4. Packing group: I
Hazard label: 3



Special Provisions: 163 367
Limited quantity: 500 mL
Excepted quantity: E3
EmS: F-E, S-E

Safety Data Sheet

according to Regulation (EC) No 1907/2006




PU140

Revision date: 11.02.2024

Page 9 of 10

Air transport (ICAO-TI/IATA-DGR)

14.1. UN number:	UN 1263
14.2. UN proper shipping name:	PAINT
14.3. Transport hazard class(es):	3
14.4. Packing group:	I
Hazard label:	3
	
Special Provisions:	A3 A72 A192
Limited quantity Passenger:	Forbidden
Passenger LQ:	Forbidden
Excepted quantity:	E3
IATA-packing instructions - Passenger:	351
IATA-max. quantity - Passenger:	1 L
IATA-packing instructions - Cargo:	361
IATA-max. quantity - Cargo:	30 L

14.5. Environmental hazards

ENVIRONMENTALLY HAZARDOUS: No

14.7. Maritime transport in bulk according to IMO instruments

No transport as bulk according to IBC Code.

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

EU regulatory information

Restrictions on use (REACH, annex XVII):

Entry 3, Entry 75

Directive 2004/42/EC on VOC in paints and varnishes: 50 %

Information according to Directive 2012/18/EU (SEVESO III): Not subject to 2012/18/EU (SEVESO III)

National regulatory information

Employment restrictions: Observe restrictions to employment for juveniles according to the 'juvenile work protection guideline' (94/33/EC). Observe employment restrictions under the Maternity Protection Directive (92/85/EEC) for expectant or nursing mothers.

Water hazard class (D): 3 - highly hazardous to water

15.2. Chemical safety assessment

For this substance a chemical safety assessment has not been carried out.

SECTION 16: Other information

Changes

This data sheet contains changes from the previous version in section(s): 6,7.

Classification for mixtures and used evaluation method according to Regulation (EC) No 1272/2008 [CLP]

Classification	Classification procedure
Flam. Liq. 3; H226	On basis of test data
Carc. 1B; H350	Calculation method

Safety Data Sheet

according to Regulation (EC) No 1907/2006



PU140

Revision date: 11.02.2024

Page 10 of 10

Relevant H and EUH statements (number and full text)

H226	Flammable liquid and vapour.
H301	Toxic if swallowed.
H312	Harmful in contact with skin.
H315	Causes skin irritation.
H317	May cause an allergic skin reaction.
H318	Causes serious eye damage.
H319	Causes serious eye irritation.
H336	May cause drowsiness or dizziness.
H350	May cause cancer.
H370	Causes damage to organs.
H373	May cause damage to organs through prolonged or repeated exposure.
H400	Very toxic to aquatic life.
H412	Harmful to aquatic life with long lasting effects.
EUH208	Contains butanone oxime; ethyl methyl ketoxime; ethyl methyl ketone oxime, Cobaltoctoat. May produce an allergic reaction.

Further Information

The information is based on the present level of our knowledge. It does not, however, give assurance of product properties and establishes no contract legal rights.

The receiver of our product is singularly responsible for adhering to existing laws and regulations.

Identified uses

No	Short title	LCS	SU	PC	PROC	ERC	AC	TF	Specification
1	Klebstoff	-	-	-	-	-	-	-	

LCS: Life cycle stages

SU: Sectors of use

PC: Product categories

PROC: Process categories

ERC: Environmental release categories

AC: Article categories

TF: Technical functions

(The data for the relevant ingredients were taken respectively from the last version of the sub-contractor's safety data sheet.)