

EP150

Revision date: 11.02.2024

Page 1 of 10

1. Identification

Product identifier

EP150

Relevant identified uses of the substance or mixture and uses advised against

Use of the substance/mixture

Adhesives, sealants

Details of the supplier of the safety data sheet

Company name: Hottinger Brüel & Kjaer
Street: Im Tiefen See 45
Place: D-64293 Darmstadt
Telephone: +49 (0)6151 803-0
Internet: www.hbm.com
Responsible Department: +49(0)6131 19240 support@hbm.com

Emergency telephone number: 1703-741-5970

2. Hazard identification

Classification of the substance or mixture

Regulation (EC) No 1272/2008

Flam. Liq. 2; H225
Skin Irrit. 2; H315
Eye Irrit. 2; H319
Skin Sens. 1; H317
STOT SE 3; H336
Aquatic Chronic 3; H412

Full text of hazard statements: see SECTION 16.

Label elements

Regulation (EC) No 1272/2008

Signal word: Danger

Pictograms:



Hazard statements

H225 Highly flammable liquid and vapour.
H315 Causes skin irritation.
H317 May cause an allergic skin reaction.
H319 Causes serious eye irritation.
H336 May cause drowsiness or dizziness.
H412 Harmful to aquatic life with long lasting effects.

Precautionary statements

P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
P261 Avoid breathing dust/fume/gas/mist/vapours/spray.
P280 Wear protective gloves/protective clothing/eye protection/face protection.

Special labelling of certain mixtures

Restricted to professional users.

Labelling of packages where the contents do not exceed 125 ml

Signal word: Danger

EP150

Revision date: 11.02.2024

Page 2 of 10

Pictograms:**Hazard statements**

H317-H412

Precautionary statements

P261-P280

Other hazards

No information available.

3. Composition/information on ingredients**Mixtures****Hazardous components**

CAS No	Chemical name	Quantity
78-93-3	butanone; ethyl methyl ketonebutanone; ethyl methyl ketone	35 - < 40 %
25068-38-6	reaction product: bisphenol-A-(epichlorhydrin); epoxy resin (number average molecular weight <= 700)	20 - < 25 %
123-42-2	4-hydroxy-4-methylpentan-2-one; diacetone alcohol	15 - < 20 %
1330-20-7	xylene	10 - < 15 %
80-08-0	dapsone; 4,4'-diamino diphenyl sulfone	5 - < 10 %

Full text of H statements: see section 16.

Specific Conc. Limits, M-factors and ATE

CAS No	EC No	Chemical name	Quantity
		Specific Conc. Limits, M-factors and ATE	
25068-38-6	500-033-5	reaction product: bisphenol-A-(epichlorhydrin); epoxy resin (number average molecular weight <= 700)	20 - < 25 %
		Skin Irrit. 2; H315: >= 5 - 100 Eye Irrit. 2; H319: >= 5 - 100	
123-42-2	204-626-7	4-hydroxy-4-methylpentan-2-one; diacetone alcohol	15 - < 20 %
		dermal: LD50 = 13630 mg/kg; oral: LD50 = 2520 mg/kg Eye Irrit. 2; H319: >= 10 - 100	
1330-20-7	215-535-7	xylene	10 - < 15 %
		inhalation: ATE = 11 mg/l (vapours); inhalation: ATE = 1,5 mg/l (dusts or mists); dermal: ATE = 1100 mg/kg	
80-08-0	201-248-4	dapsone; 4,4'-diamino diphenyl sulfone	5 - < 10 %
		oral: ATE = 500 mg/kg	

Further Information

No information available.

4. First-aid measures**Description of first aid measures****General information**

Remove affected person from the danger area and lay down. If unconscious but breathing normally, place in recovery position and seek medical advice. First aider: Pay attention to self-protection!

After inhalation

Provide fresh air.

If experiencing respiratory symptoms: Call a doctor.

After contact with skin

After contact with skin, wash immediately with plenty of water and soap.

EP150

Revision date: 11.02.2024

Page 3 of 10

After contact with eyes

After contact with the eyes, rinse with water with the eyelids open for a sufficient length of time, then consult an ophthalmologist immediately.

After ingestion

Rinse mouth immediately and drink plenty of water. Do NOT induce vomiting. Call a doctor if you feel unwell.

Most important symptoms and effects, whether acute or delayed

No information available.

Indication of immediate medical attention and special treatment needed

Treat symptomatically.

5. Fire-fighting measures**Extinguishing media****Suitable extinguishing media**

Carbon dioxide (CO₂) Extinguishing powder, Foam

Unsuitable extinguishing media

Full water jet

Specific hazards arising from the hazardous product

Highly flammable Vapours can form explosive mixtures with air.

Special protective equipment and precautions for fire-fighters

Self-contained respirator (breathing apparatus)

Full protection suit

Additional information

Use water spray jet to protect personnel and to cool endangered containers.

Suppress gases/vapours/mists with water spray jet.

Do not empty into drains.

6. Accidental release measures**Personal precautions, protective equipment and emergency procedures****General advice**

Remove all sources of ignition.

Do not breathe gas/fumes/vapour/spray. Avoid contact with skin, eyes and clothes.

Use personal protection equipment.

For non-emergency personnel

Remove persons to safety.

For emergency responders

First aider: Pay attention to self-protection!

Environmental precautions

Do not allow uncontrolled discharge of product into the environment.

Methods and material for containment and cleaning up**For cleaning up**

Take up mechanically, placing in appropriate containers for disposal.

Other information

Absorb with liquid-binding material (sand, diatomaceous earth, acid- or universal binding agents). . Treat the recovered material as prescribed in the section on waste disposal.

Reference to other sections

Safe handling: see section 7

Wear personal protection equipment (refer to section 8).

Disposal: see section 13

EP150

Revision date: 11.02.2024

Page 4 of 10

7. Handling and storage

Precautions for safe handling

Advice on safe handling

If handled uncovered, arrangements with local exhaust ventilation have to be used. Do not breathe gas/fumes/vapour/spray.

Advice on protection against fire and explosion

Keep away from sources of ignition - No smoking.
Take precautionary measures against static discharges.
Vapours can form explosive mixtures with air.

Further information on handling

Keep container tightly closed in a cool, well-ventilated place.
Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.

Conditions for safe storage, including any incompatibilities

Requirements for storage rooms and vessels

Keep container tightly closed and in a well-ventilated place.
Do not allow to enter into surface water or drains.
Do not allow uncontrolled discharge of product into the environment.

Hints on joint storage

Do not store together with: Oxidising agent, strong , Combustible substances of acute toxicity, category 1 and 2 / very toxic substances Non-combustible substances of acute toxicity, category 1 and 2 / very toxic substances

Further information on storage conditions

Keep container tightly closed in a cool, well-ventilated place.

8. Exposure controls/Personal protection

Control parameters

Additional advice on limit values

No information available.

Exposure controls



Appropriate engineering controls

If handled uncovered, arrangements with local exhaust ventilation should be used if possible.
In use, may form flammable/explosive vapour-air mixture.
Use explosion-proof electrical equipment.
Use non-sparking tools.

Protective and hygiene measures

When using do not eat or drink.
Do not breathe gas/fumes/vapour/spray.
After contact with skin, take off immediately all contaminated clothing, and wash immediately with plenty of water and soap.
Wear suitable protective clothing, gloves and eye/face protection.
Draw up and observe skin protection programme.

Eye/face protection

Wear eye/face protection.

Hand protection

When handling with chemical substances, protective gloves must be worn with the CE-label including the four

EP150

Revision date: 11.02.2024

Page 5 of 10

control digits. EN ISO 374

The quality of the protective gloves resistant to chemicals must be chosen as a function of the specific working place concentration and quantity of hazardous substances.

Thickness of the glove material: $\geq 0,7\text{mm}$

Suitable gloves type NBR (Nitrile rubber)

Breakthrough time: $>480\text{ min}$

For special purposes, it is recommended to check the resistance to chemicals of the protective gloves mentioned above together with the supplier of these gloves.

Skin protection

Used working clothes should not be worn outside the work area.

Separate storage of work clothes.

Wear anti-static footwear and clothing

Respiratory protection

If technical exhaust or ventilation measures are not possible or insufficient, respiratory protection must be worn. Filtering device (full mask or mouthpiece) with filter: a

The filter class must be suitable for the maximum contaminant concentration (gas/vapour/aerosol/particulates) that may arise when handling the product. If the concentration is exceeded, self-contained breathing apparatus must be used.

Environmental exposure controls

Do not allow to enter into surface water or drains.

The vapour of the product is heavier than air and may accumulate below ground level, in pits, channels and basements in higher concentration.

9. Physical and chemical properties**Information on basic physical and chemical properties**

Physical state:	Liquid	
Colour:	transparent	
Odour:	Adhesives, sealants	
pH-Value:		not determined

Changes in the physical state

Melting point/freezing point:		not determined
Boiling point or initial boiling point and boiling range:		80 °C
Sublimation point:		not determined
Softening point:		not determined
Pour point:		not determined
not determined:		

Flash point:		-4 °C
Sustaining combustion:		No data available

Flammability

Solid/liquid:		not applicable
---------------	--	----------------

Explosive properties

Es liegen keine Informationen vor.

Lower explosive limits:		0,7 vol. %
Upper explosive limits:		11,5 vol. %
Auto-ignition temperature:		465 °C

Self-ignition temperature

Solid:		not applicable
Gas:		not applicable

EP150

Revision date: 11.02.2024

Page 6 of 10

Decomposition temperature: not determined

Oxidizing properties

Nicht brandfördernd.

Vapour pressure:
(at 20 °C) 8 hPaVapour pressure:
(at 50 °C) 9 hPaDensity (at 20 °C): 0,934 g/cm³

Bulk density: not determined

Water solubility: The study does not need to be conducted
because the substance is known to be
insoluble in water.**Solubility in other solvents**

nicht bestimmt

Partition coefficient n-octanol/water: not determined

Viscosity / dynamic: not determined

Viscosity / kinematic: not determined

Flow time: not determined

Relative vapour density: not determined

Evaporation rate: not determined

Solvent separation test: not determined

Solvent content: 69,50 %

Other information

Solid content: not determined

10. Stability and reactivity**Reactivity**

Highly flammable

Chemical stability

The product is stable under storage at normal ambient temperatures.

Possibility of hazardous reactions

No known hazardous reactions.

Conditions to avoid

Keep away from sources of heat (e.g. hot surfaces), sparks and open flames.

Vapours can form explosive mixtures with air.

Incompatible materials

No information available.

Hazardous decomposition products

No known hazardous decomposition products.

Further information

No information available.

11. Toxicological information**Information on toxicological effects****Acute toxicity**

Based on available data, the classification criteria are not met.

EP150

Revision date: 11.02.2024

Page 7 of 10

ATEmix calculated

ATE (oral) 8333 mg/kg; ATE (dermal) 8462 mg/kg; ATE (inhalation vapour) 84,62 mg/l; ATE (inhalation dust/mist) 11,54 mg/l

CAS No	Chemical name				
	Route of exposure	Dose	Species	Source	Method
123-42-2	4-hydroxy-4-methylpentan-2-one; diacetone alcohol				
	oral	LD50 mg/kg	2520	Rat	
	dermal	LD50 mg/kg	13630	Rabbit	
1330-20-7	xylene				
	dermal	ATE mg/kg	1100		
	inhalation vapour	ATE	11 mg/l		
	inhalation dust/mist	ATE	1,5 mg/l		
80-08-0	dapsone; 4,4'-diamino diphenyl sulfone				
	oral	ATE mg/kg	500		

Irritation and corrosivity

Causes skin irritation.

Causes serious eye irritation.

Sensitizing effects

May cause an allergic skin reaction. (reaction product: bisphenol-A-(epichlorhydrin); epoxy resin (number average molecular weight <= 700))

Carcinogenic/mutagenic/toxic effects for reproduction

Based on available data, the classification criteria are not met.

STOT-single exposure

May cause drowsiness or dizziness. (butanone; ethyl methyl ketonebutanone; ethyl methyl ketone)

STOT-repeated exposure

Based on available data, the classification criteria are not met.

Aspiration hazard

Based on available data, the classification criteria are not met.

Specific effects in experiment on an animal

No information available.

Additional information on tests

No information available.

Practical experience

No information available.

Information on other hazards**Endocrine disrupting properties**

This product does not contain a substance that has endocrine disrupting properties with respect to non-target organisms as no components meets the criteria.

Other information

No information available.

Further information

No information available.

12. Ecological information

EP150

Revision date: 11.02.2024

Page 8 of 10

Ecotoxicity

No information available.

Persistence and degradability

No information available.

Bioaccumulative potential

No information available.

Mobility in soil

No information available.

Endocrine disrupting properties

This product does not contain a substance that has endocrine disrupting properties with respect to non-target organisms as no components meets the criteria.

Other adverse effects

No information available.

Further information

Do not allow to enter into surface water or drains.

13. Disposal considerations**Waste treatment methods****Disposal recommendations**

Dispose of waste according to applicable legislation.

Contaminated packaging

Non-contaminated packages may be recycled.

14. Transport information**Canadian TDG**

<u>UN number or ID number:</u>	UN 1133
<u>Proper shipping name:</u>	Adhesives
<u>Hazard classes:</u>	3
<u>Packing group:</u>	III
Hazard label:	3
Limited quantity:	5L

**Marine transport (IMDG)**

<u>UN number:</u>	UN 1133
<u>United Nations proper shipping name:</u>	ADHESIVES
<u>Transport hazard class(es):</u>	3
<u>Packing group:</u>	III
Hazard label:	3



Special Provisions:	223 955
Limited quantity:	5 L

EP150

Revision date: 11.02.2024

Page 9 of 10

Excepted quantity: E1
EmS: F-E, S-D

Air transport (ICAO-TI/IATA-DGR)

UN number: UN 1133
United Nations proper shipping name: ADHESIVES
Transport hazard class(es): 3
Packing group: III
Hazard label: 3



Special Provisions: A3
Limited quantity Passenger: 10 L
Passenger LQ: Y344
Excepted quantity: E1
IATA-packing instructions - Passenger: 355
IATA-max. quantity - Passenger: 60 L
IATA-packing instructions - Cargo: 366
IATA-max. quantity - Cargo: 220 L

Environmental hazards

ENVIRONMENTALLY HAZARDOUS: No

15. Regulatory information

Canadian regulations

16. Other information

Changes

This data sheet contains changes from the previous version in section(s): 6.

Abbreviations and acronyms

- ADR: Accord européen sur le transport des marchandises dangereuses par Route (European Agreement concerning the International Carriage of Dangerous Goods by Road)
- IMDG: International Maritime Code for Dangerous Goods
- IATA: International Air Transport Association
- GHS: Globally Harmonized System of Classification and Labelling of Chemicals
- EINECS: European Inventory of Existing Commercial Chemical Substances
- ELINCS: European List of Notified Chemical Substances
- CAS: Chemical Abstracts Service
- LC50: Lethal concentration, 50%
- LD50: Lethal dose, 50%

Classification for mixtures and used evaluation method according to regulation (EC) No 1272/2008

Classification	Classification procedure
Flam. Liq. 2; H225	On basis of test data
Skin Irrit. 2; H315	Calculation method
Eye Irrit. 2; H319	Calculation method
Skin Sens. 1; H317	Calculation method
STOT SE 3; H336	Calculation method
Aquatic Chronic 3; H412	Calculation method

Relevant H statements (number and full text)

H225	Highly flammable liquid and vapour.
H226	Flammable liquid and vapour.
H302	Harmful if swallowed.
H312	Harmful in contact with skin.
H315	Causes skin irritation.
H317	May cause an allergic skin reaction.
H319	Causes serious eye irritation.
H332	Harmful if inhaled.
H336	May cause drowsiness or dizziness.
H411	Toxic to aquatic life with long lasting effects.
H412	Harmful to aquatic life with long lasting effects.
EUH066	Repeated exposure may cause skin dryness or cracking.

Further Information

The information is based on the present level of our knowledge. It does not, however, give assurance of product properties and establishes no contract legal rights.

The receiver of our product is singularly responsible for adhering to existing laws and regulations.

(The data for the relevant ingredients were taken respectively from the last version of the sub-contractor's safety data sheet.)